


INDUSTRIAL GAS BOOSTER | PROFESSIONAL

MODEL	Model GBT-D15/75-REX
SERIES	<p>GBT-D Series</p> <p>Two Stage- Double Head</p> <p>Has same characteristics of the standard GBT however the double allows half the input pressure to achieve the same outlet pressure</p> <p>Nitrogen, Oxygen, Argon, Helium, Hydrogen and more.</p>



PERFORMANCE CHART



COMFORTABLE

MAX. RATED OPERATIONAL

Output Pressure	16000 Psi (1103 Bar)	Max. Output Pressure	25,000 Psi (1723 Bar)
Gas Input	100 - 500 Psi	Max. Gas Input	800 - 5000 Psi
Volume Per Stroke	7.5 in ³	Volume Per Stroke	7.5 in ³
Flow	50-250 LPM	Flow	200 LPM
Air Operate	60 - 90 psi (6 bar)	Air Operate	100 - 120 psi (7 bar)
Max. Air Consumption	72-scfm		

Refer to gas booster performance curve for operating pressures

CONSTRUCTION & GASES

Variety Gases	Nitrogen, Oxygen, Argon, Helium, Hydrogen and more.
Pump Brand	SC-Hydraulic Engineering
Made In	USA
Components	Parker, McDaniel, Spir Star & Swagelok
Frame	Steel painted frame (Painted Blue) + Stainless steel Control Panel
Dimensions & Weight	29" L X 14" W X 17"H - Shipping Weight 100 lbs

FEATURES

- Infinitely variable output pressure and flow
- Will hold static pressure without generating heat or consuming power
- Standard models are suitable for various gases
- Well proven and trouble-free operation
- Designed for ease of maintenance
- Low cost servicing
- Robust construction

CONNECTIONS

Gas Inlet	1/4" NPT Female
Gas Outlet	3/8" MP Female
Air Inlet	3/8" NPT Female
Pressure Hoses	20,000 Psi - M9 Swivel Nuts - 20ft

PUMP ON MODEL GBD-5-REX - DRAWING

